



COLLAK R-7766

High Quality Neoprene Contact Adhesive



DESCRIPTION: Good quality Polychloroprene contact adhesive for general purpose in DIY and industrial applications. Combination bonding of a wide range of porous and non-porous materials such as; wood, wood materials with plastic laminates, rubber, leather, cork, felt, hard PVC, flexible foam materials, metals, ceramics, etc. Not suitable for polystyrene.

TECHNICAL DATA	
Colour:	Amber
Specific gravity:	0,80 - 0,90 gr/ml
Solid content:	24 ± 1 %
Viscosity: (Ford # 8, 20 °C)	60 - 90 sec.
Coverage:	200 - 300 gr/m ² approx.

APPLICATION: Stir adhesive well before use and apply uniformly to both surfaces (double stick) with a notched trowel or brush. Surfaces must be clean, dry and free of grease. Allow both surfaces to become dry / tacky to the touch, approx. 10 – 15 minutes at normal ambient conditions, before joining both surfaces. Do not entrap solvent. Note that the bond is made upon contact and that once done it is no possible to rectify. Working time is 45 minutes approx.

CLEANING: Clean tools or excess adhesive with COLLAK D-0.

HEALTH & SAFETY: This adhesive contains solvent and is therefore highly flammable. Avoid naked flame. Avoid inhalation and contact with skin. Ensure adequate ventilation during use. Where appropriate, wear suitable Personal Protective Equipment (e.g. gloves, eyes protection, etc.) For further advice, please read the Safety Data Sheet of our adhesive, available upon request.

PACKAGING AND STORAGE: In 125 ml tube and 250 ml, 500 ml, 1, 5 and 25 L cans. The shelf life is 12 months in the closed original packaging stored at normal ambient conditions (e.g. 20°C and 55% relative humidity).