

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 1 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: COLLAK ALU-SIL BLANCO
UFI: R3C0-60A7-S00N-5FXM

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Sealant

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **COLLAK, S.A.**
Address: C/ FRANCIA Nº 3 - POL. LLERONA
City: 08520 - LES FRANQUESES DEL VALLÈS
Province: BARCELONA
Telephone: 93 849 44 33
Fax: 93 849 22 77
E-mail: collak@collak.com
Web: www.collak.com

1.4 Emergency telephone number: 93 849 44 33 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Asp. Tox. 1 : May be fatal if swallowed and enters airways.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container to an habilitated place for packages that contains chemical products.

EUH statements:

EUH208 Contains Butan-2-one O,O',O''-(methylsilyldiylidene)trioxime. May produce an allergic reaction.
EUH208 Contains 3-(2-aminoethylamino)propyltrimethoxysilane. May produce an allergic reaction.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 2 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

Contains:
Alcarilsulfonato de calcio de cadena larga

2.3 Other hazards.

Identifiers	Name	PBT,vPvB or endocrine disrupting properties substances (concentration >=0,1%)
CAS No: 540-97-6 EC No: 208-762-8	dodecamethylcyclhexasiloxane	vPvB substance

mPmB: muy Persistente y muy Bioacumulable.

The mixture does not contain substances classified as PBT.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Registration No: 01-2119827000-58	Alcarilsulfonato de calcio de cadena larga	10 - 25 %	Asp. Tox. 1, H304	-
CAS No: 22984-54-9 EC No: 245-366-4 Registration No: 01-2119987100-43-0000	Butan-2-one O,O',O''-(methylsilyldiylne)trioxime	0.1 - 1 %	Eye Dam. 1, H318 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 1760-24-3 EC No: 217-164-6 Registration No: 01-2119970215-39-XXXX	3-(2-aminoethylamino)propiltrimethoxysilane	0.1 - 1 %	Eye Dam. 1, H318 - Skin Sens. 1B, H317 - STOT SE 3, H335	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	0.04 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 540-97-6 EC No: 208-762-8 Registration No: 01-2119517435-42-XXXX	[4] [5] dodecamethylcyclhexasiloxane	0.04 - 2.5 %	-	-
Index No: 050-030-00-3 CAS No: 77-58-7 EC No: 201-039-8 Registration No: 01-2119496068-27-XXXX	Dibutyltin dilaurate, dibutyl[bis(dodecanoyloxy)] stannane	0.1 - 0.3 %	Muta. 2, H341 - Repr. 1B, H360 - STOT RE 1, H372	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 3 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

[2] Substance with a national workplace exposure limit (see section 8.1).

[4] vPvB Substance (very Persistent and very Bioaccumulative).

[5] Substance included in the list established under Article 59, paragraph 1, REACH (Candidate substance).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

The product is NOT classified as flammable, in case of fire the following measures should be taken:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 4 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Acristalamiento y sellado en general

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)
dodecamethylcyclhexasiloxane CAS No: 540-97-6 EC No: 208-762-8	DNEL (Workers)	Inhalation, Chronic, Systemic effects	98 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 5 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	Sealant		
Breathing protection:			
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Work footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN 20347		
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.		
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Blanco

Odour: Característico

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 6 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

Freezing point: Not applicable/Not available due to the nature/properties of the product
Boiling point or initial boiling point and boiling range: Not applicable/Not available due to the nature/properties of the product
Flammability: Combustible
Lower explosion limit: Not applicable/Not available due to the nature/properties of the product
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: > 60 °C
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable (Substance/mixture reacts with water).
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: No soluble
Liposolubility: Sin determinar
Partition coefficient n-octanol/water (log value): Sin determinar
Vapour pressure: Sin determinar
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: aprox. 1.01-1.03
Relative vapour density: Sin determinar
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Explosives:

Explosive properties: No aplicable

Oxidising liquids:

Oxidizing properties: No aplicable

Other safety characteristics

Viscosity: Alta tixotropía

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

There are no tested data available on the product.

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		  Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 7 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

d) respiratory or skin sensitisation;
Based on available data, the classification criteria are not met.

e) germ cell mutagenicity;
Based on available data, the classification criteria are not met.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Based on available data, the classification criteria are not met.

h) STOT-single exposure;
Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Product classified:
Aspiration toxicity, Category 1: May be fatal if swallowed and enters airways.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1	Date of compilation: 30/06/2021	Page 8 of 10 Print date: 07/09/2023
Version 1.1 (replaces version 1.0)	Revision date: 06/09/2023	

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number or ID number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR/RID: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): Not applicable.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Maritime transport in bulk according to IMO instruments.

Not classified as hazardous for transport.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

VOC content (p/p): 2,14 %

VOC content: 20,473 g/l

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

Substances including by Regulation (EU) No 649/2012 concerning the export and import of dangerous chemicals:

Name	
Dibutyltin dilaurate; dibutyl[bis(dodecanoyloxy)] stannane	
CAS No: 77-58-7	
EC No: 201-039-8	
Annex I Part 1 - Subcategory	Limitation
Industrial chemical for public use	Severe restriction

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

-Continued on next page.-

SAFETY DATA SHEET (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
COLLAK ALU-SIL BLANCO		
Version 1 Version 1.1 (replaces version 1.0)	Date of compilation: 30/06/2021 Revision date: 06/09/2023	Page 9 of 10 Print date: 07/09/2023

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Flam. Liq. 3 : Flammable liquid, Category 3
Muta. 2 : Mutagen, Category 2
Repr. 1B : Reproductive toxicant, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Changes in the composition of the product (SECTION 3.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Change in the hazard classification (SECTION 11.1).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
PPE:	Personal protection equipment.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>
<http://echa.europa.eu/>
Regulation (EU) 2020/878.
Regulation (EC) No 1907/2006.
Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



COLLAK ALU-SIL BLANCO

Version 1 **Date of compilation: 30/06/2021**

Version 1.1 (replaces version 1.0)

Revision date: 06/09/2023

Page 10 of 10

Print date: 07/09/2023

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.