

COLLAK R-7520

1. DESCRIPTION

Synthetic rubber based adhesive. High adhesive strength.

2. APPLICATIONS

Contact adhesive specially formulated to fix insulating flexible shells.

2. TECHNICAL DATA

Waiting time: approx. 3-5 minutes.

Working time: approx. 10 minutes.

PROPEY	VALUE
Colour	Amber
Specific gravity	0,80 - 0,90 g/ml
Viscosity (Ford Nº 8, 20 °C)	100 - 120 s
Coverage	200 - 300 g/m ² approx.

3. INSTRUCTIONS FOR USE

Stir adhesive well before use and apply uniformly to both surfaces (double stick) with a notched trowel or brush. Surfaces must be clean, dry and free of grease. Allow both surfaces to become dry / tacky to the touch, approx. 3 – 5 minutes at normal ambient conditions, before joining both surfaces. Do not entrap solvent. Note that the bond is made upon contact and that once done it is no possible to rectify. Working time is 10 minutes approx.

Clean tools or excess adhesive with COLLAK D-0.

4. PRESENTATION

In 250 ml, 500 ml or 1000 mL drums with cap brush.

5. STORAGE

The shelf life is 12 months in the closed original packaging stored at normal ambient conditions (e.g. 20°C and 55% relative humidity) protected from frost.

6. CAUTIONS

This adhesive contains solvent and is therefore highly flammable. Avoid naked flame. Avoid inhalation and contact with skin. Ensure adequate ventilation during use. Where appropriate, wear suitable Personal Protective Equipment (e.g. gloves, eyes protection, etc.) For further advice, please read the Safety Data Sheet of our adhesive, available upon request.