

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

## R-7520



Version 1 Date of compilation: 8/10/2018  
Version 1.0 (replaces version 1) Revision date: 13/05/2022

Page 1 of 13  
Print date: 21/11/2022

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: R-7520

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

Adhesive

#### Uses advised against:

Uses other than those recommended.

#### 1.3 Details of the supplier of the safety data sheet.

Company: **COLLAK, S.A.**  
Address: C/ FRANCIA Nº 3 - POL. LLERONA  
City: 08520 - LES FRANQUESES DEL VALLÈS  
Province: BARCELONA  
Telephone: 93 849 44 33  
Fax: 93 849 22 77  
E-mail: collak@collak.com  
Web: www.collak.com

#### 1.4 Emergency telephone number: 93 849 44 33 (Only available during office hours)

### SECTION 2: HAZARDS IDENTIFICATION.

#### 2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Acute 1 : Very toxic to aquatic life.  
Aquatic Chronic 1 : Very toxic to aquatic life with long lasting effects.  
Asp. Tox. 1 : May be fatal if swallowed and enters airways.  
Eye Irrit. 2 : Causes serious eye irritation.  
Flam. Liq. 2 : Highly flammable liquid and vapour.  
Skin Irrit. 2 : Causes skin irritation.  
Skin Sens. 1 : May cause an allergic skin reaction.  
STOT SE 3 : May cause drowsiness or dizziness.

#### 2.2 Label elements.

##### Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:




Signal Word:

**Danger**

Hazard statements:

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 2 of 13</b> <b>Print date: 21/11/2022</b>

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P501	Dispose of contents/container to places habilitated by local authorities.

Contains:

Resina fenólica  
cyclohexane  
butanone, ethyl methyl ketone  
ethyl acetate

**2.3 Other hazards.**

The mixture does not contain substances classified as PBT.  
The mixture does not contain substances classified as vPvB.  
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.**

**3.1 Substances.**


Not Applicable.

**3.2 Mixtures.**

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 606-002-00-3 CAS No: 78-93-3 EC No: 201-159-0 Registration No: 01-2119457290-43-XXXX	[1] [2] butanone, ethyl methyl ketone	20 - 50 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
Index No: 601-017-00-1 CAS No: 110-82-7 EC No: 203-806-2 Registration No: 01-2119463273-41-XXXX	[1] [2] cyclohexane	25 - 50 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - Skin Irrit. 2, H315 - STOT SE 3, H336	-
Index No: 607-022-00-5 CAS No: 141-78-6 EC No: 205-500-4 Registration No: 01-2119475103-46-XXXX	[1] [2] ethyl acetate	10 - 20 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b>	<b>Date of compilation: 8/10/2018</b>	<b>Page 3 of 13</b> <b>Print date: 21/11/2022</b>
<b>Version 1.0 (replaces version 1)</b>	<b>Revision date: 13/05/2022</b>	

CAS No: 59633-97-5	Resina fenólica	1 - 10 %	Skin Sens. 1B, H317	-
CAS No: 1309-48-4 EC No: 215-171-9	[2] magnesium oxide	0.04 - 2.5 %	-	-
CAS No: 128-37-0 EC No: 204-881-4 Registration No: 01-2119565113-46-XXXX	[2] 2,6-di-tert-butyl-p-cresol	0.25 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

#### SECTION 4: FIRST AID MEASURES.

**IRRITANT MIXTURE.** Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

##### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

##### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

##### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

##### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

##### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

##### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

##### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

#### SECTION 5: FIREFIGHTING MEASURES.


The product is Highly flammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

##### 5.1 Extinguishing media.

##### Suitable extinguishing media:

Extinguisher powder or CO<sub>2</sub>. In case of more serious fires, also alcohol-resistant foam and water spray.

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 4 of 13</b> <b>Print date: 21/11/2022</b>

**Unsuitable extinguishing media:**

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

**5.2 Special hazards arising from the substance or mixture.**

**Special risks.**

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Carbon monoxide, carbon dioxide.
- Flammable vapors or gases.

**5.3 Advice for firefighters.**

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

**Fire protection equipment.**

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

**SECTION 6: ACCIDENTAL RELEASE MEASURES.**

**6.1 Personal precautions, protective equipment and emergency procedures.**

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

**6.2 Environmental precautions.**

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

**6.3 Methods and material for containment and cleaning up.**

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

**6.4 Reference to other sections.**

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

**SECTION 7: HANDLING AND STORAGE.**

**7.1 Precautions for safe handling.**

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.


Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

**7.2 Conditions for safe storage, including any incompatibilities.**

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 5 of 13</b> <b>Print date: 21/11/2022</b>

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200
E1	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Acute 1 or Chronic 1	100	200

### 7.3 Specific end use(s).

Pegado de coquillas en aislamiento

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
butanone, ethyl methyl ketone	78-93-3	European Union [1]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	900
		United Kingdom [2]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	899
		Éire [3]	<b>Eight hours</b>	200	600
			<b>Short term</b>	300	900
		United States [4] (Cal/OSHA)	<b>Eight hours</b>	200	
			<b>Short term</b>	300	
		United States [5] (NIOSH)	<b>Eight hours</b>	200	
			<b>Short term</b>	300	
		United States [6] (OSHA)	<b>Eight hours</b>	200	590
			<b>Short term</b>		
cyclohexane	110-82-7	European Union [1]	<b>Eight hours</b>	200	700
			<b>Short term</b>		
		United Kingdom [2]	<b>Eight hours</b>	100	350
			<b>Short term</b>	300	1050
		Éire [3]	<b>Eight hours</b>	200	700
			<b>Short term</b>		
		United States [4] (Cal/OSHA)	<b>Eight hours</b>	300	
			<b>Short term</b>		
		United States [5] (NIOSH)	<b>Eight hours</b>	300	
			<b>Short term</b>		
		United States [6] (OSHA)	<b>Eight hours</b>	300	1050
			<b>Short term</b>		
ethyl acetate	141-78-6	European Union [1]	<b>Eight hours</b>	200	734
			<b>Short term</b>	400	1468
		United Kingdom [2]	<b>Eight hours</b>	200	
			<b>Short term</b>	400	
		Éire [3]	<b>Eight hours</b>	200	734
			<b>Short term</b>	400	1468
		United States [4] (Cal/OSHA)	<b>Eight hours</b>	400	
			<b>Short term</b>		
		United States	<b>Eight hours</b>	400	
			<b>Short term</b>		

-Continued on next page.-

# SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



**R-7520**

**Version 1**      **Date of compilation: 8/10/2018**

**Version 1.0 (replaces version 1)**

**Revision date: 13/05/2022**

**Page 6 of 13**

**Print date: 21/11/2022**

		[5] (NIOSH)	<b>Short term</b>		
		United States	<b>Eight hours</b>	400	1400
		[6] (OSHA)	<b>Short term</b>		
magnesium oxide	1309-48-4	United Kingdom [2]	<b>Eight hours</b>		10 (inhalable dust) 4 (fume and respirable dust)
			<b>Short term</b>		
		Éire [3]	<b>Eight hours</b>		4 (respirable dust) 5 (fume) 10 (inhalable dust)
			<b>Short term</b>		10 (fume)
		United States [4] (Cal/OSHA)	<b>Eight hours</b>		10 (fume - Total Particulate)
			<b>Short term</b>		
2,6-di-tert-butyl-p-cresol	128-37-0	United States [6] (OSHA)	<b>Eight hours</b>		15 (fume - Total Particulate)
			<b>Short term</b>		
		United Kingdom [2]	<b>Eight hours</b>		10
			<b>Short term</b>		
		Éire [3]	<b>Eight hours</b>		2
			<b>Short term</b>		

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[3] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[4] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[5] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.


[6] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Workers)	Inhalation, Chronic, Systemic effects	600 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Chronic, Systemic effects	1161 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	31 (mg/kg bw/day)
	DMEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m <sup>3</sup> )
	DMEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/m <sup>3</sup> )
	DMEL (Consumers)	Inhalation, Chronic, Systemic effects	700 (mg/m <sup>3</sup> )
cyclohexane CAS No: 110-82-7 EC No: 203-806-2	DNEL (Workers)	Inhalation, Chronic, Local effects	700 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	700 (mg/m <sup>3</sup> )
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Chronic, Local effects	734 (mg/m <sup>3</sup> )

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 7 of 13</b> <b>Print date: 21/11/2022</b>

	DNEL (Consumers)	Inhalation, Chronic, Local effects	367 (mg/m <sup>3</sup> )
	DNEL (Workers)	Inhalation, Short term, Local effects	1468 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Short term, Local effects	734 (mg/m <sup>3</sup> )
	DNEL (Workers)	Dermal, Chronic, Systemic effects	63 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	37 (mg/kg bw/day)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	3,5 (mg/m <sup>3</sup> )
2,6-di-tert-butyl-p-cresol CAS No: 128-37-0 EC No: 204-881-4			

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
	STP	709 (mg/L)
	sediment (freshwater)	284,74 (mg/kg sediment dw)
	sediment (marine water)	284,7 (mg/kg sediment dw)
	oral (Hazard for predators)	1000 (mg/kg food)
ethyl acetate CAS No: 141-78-6 EC No: 205-500-4	aqua (freshwater)	0,24 (mg/L)
	aqua (marine water)	0,024 (mg/L)
	aqua (intermittent releases)	1,65 (mg/L)
	sediment (freshwater)	1,15 (mg/L)
	sediment (marine water)	0,115 (mg/L)
	Soil	0,148 (mg/kg soil dw)
	STP	650 (mg/L)
	oral (Hazard for predators)	0,2 (g/kg food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

## 8.2 Exposure controls.


### Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

<b>Concentration:</b>	<b>100 %</b>
<b>Uses:</b>	<b>Adhesive</b>
<b>Breathing protection:</b>	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.



-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b>	<b>Date of compilation: 8/10/2018</b>	<b>Page 8 of 13</b> <b>Print date: 21/11/2022</b>
<b>Version 1.0 (replaces version 1)</b>	<b>Revision date: 13/05/2022</b>	

Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
<b>Hand protection:</b>			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
<b>Eye protection:</b>			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
<b>Skin protection:</b>			
PPE:	Anti-static protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Anti-static safety footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346		
Maintenance:	The footwear should be checked regularly		
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.		

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

### 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Transparente amarillento

Odour: Característico a cetonas e hidrocarburos

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 56 °C

Flammability: Fácilmente inflamable

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product


Flash point: -13 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable (Substance/mixture is non-soluble (in water)).

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b>	<b>Date of compilation: 8/10/2018</b>	<b>Page 9 of 13</b>
<b>Version 1.0 (replaces version 1)</b>	<b>Revision date: 13/05/2022</b>	<b>Print date: 21/11/2022</b>

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product  
Solubility: En prácticamente todos los disolventes orgánicos  
Hydrosolubility: Parcialmente soluble  
Liposolubility: Not applicable/Not available due to the nature/properties of the product  
Partition coefficient n-octanol/water (log value): Sin determinar  
Vapour pressure: Sin determinar  
Absolute density: Not applicable/Not available due to the nature/properties of the product  
Relative density: 0.8-0.9  
Relative vapour density: Sin determinar  
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

## 9.2 Other information

Viscosity: 100 s (Copa Ford nº8)(20°C)  
Explosive properties: Las mezclas vapor aire son explosivas  
Oxidizing properties: No aplicable  
Dropping point: Not applicable/Not available due to the nature/properties of the product  
Blink: Not applicable/Not available due to the nature/properties of the product

## SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

The product does not present hazards by their reactivity.

### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

### 10.4 Conditions to avoid.

Avoid any improper handling.

### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

### 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

## SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

### 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.


There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;  
Not conclusive data for classification.

b) skin corrosion/irritation;  
Product classified:  
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;  
Product classified:  
Eye irritation, Category 2: Causes serious eye irritation.

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 10 of 13</b> <b>Print date: 21/11/2022</b>

d) respiratory or skin sensitisation;  
Product classified:  
Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;  
Not conclusive data for classification.

f) carcinogenicity;  
Not conclusive data for classification.

g) reproductive toxicity;  
Not conclusive data for classification.

h) STOT-single exposure;  
Product classified:  
Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure;  
Not conclusive data for classification.

j) aspiration hazard;  
Product classified:  
Aspiration toxicity, Category 1: May be fatal if swallowed and enters airways.

#### 11.2 Information on other hazards.

##### **Endocrine disrupting properties**

This product does not contain components with endocrine-disrupting properties with effects on human health.

##### **Other information**

There is no information available on other adverse health effects.

## SECTION 12: ECOLOGICAL INFORMATION.

#### 12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

#### 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

#### 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.


Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
butanone, ethyl methyl ketone CAS No: 78-93-3      EC No: 201-159-0	0,29	-	-	Very low
ethyl acetate CAS No: 141-78-6      EC No: 205-500-4	0,73	-	-	Very low

#### 12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 11 of 13</b> <b>Print date: 21/11/2022</b>

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

#### 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

#### 12.7 Other adverse effects.

No information is available about other adverse effects for the environment.

### SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

### SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

**Sea:** Transport by ship: IMDG.

Transport documentation: Bill of lading

**Air:** Transport by plane: ICAO/IATA.

Transport document: Airway bill.

#### 14.1 UN number or ID number.

UN No: UN1133

#### 14.2 UN proper shipping name.

Description:

ADR/RID: UN 1133, ADHESIVES, 3, PG III, (E)

IMDG: UN 1133, ADHESIVES (CYCLOHEXANE), 3, PG III, MARINE POLLUTANT

ICAO/IATA: UN 1133, ADHESIVES, 3, PG III

#### 14.3 Transport hazard class(es).

Class(es): 3

#### 14.4 Packing group.

Packing group: III

#### 14.5 Environmental hazards.

Marine pollutant: Yes




Dangerous for the environment

Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-E,S-D

#### 14.6 Special precautions for user.

Labels: 3

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	



Hazard number: Not applicable.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.  
Proceed in accordance with point 6.

#### 14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

### SECTION 15: REGULATORY INFORMATION.

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

##### Volatile organic compound (VOC)

VOC content (p/p): 74,81 %

VOC content: 598,48 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b,E1

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: OTHER INFORMATION.


Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1  
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1  
Asp. Tox. 1 : Aspiration toxicity, Category 1  
Eye Irrit. 2 : Eye irritation, Category 2  
Flam. Liq. 2 : Flammable liquid, Category 2

-Continued on next page.-

<b>SAFETY DATA SHEET</b> (in accordance with Regulation (EU) 2020/878)		 Adhesivos y Selladores
<b>R-7520</b>		
<b>Version 1</b> <b>Version 1.0 (replaces version 1)</b>	<b>Date of compilation: 8/10/2018</b> <b>Revision date: 13/05/2022</b>	<b>Page 13 of 13</b> <b>Print date: 21/11/2022</b>

Skin Irrit. 2 : Skin irritant, Category 2  
Skin Sens. 1 : Skin sensitiser, Category 1  
Skin Sens. 1B : Skin sensitiser, Category 1B  
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Modification in the values of the physical and chemical properties (SECTION 9).
- National legislative changes (SECTION 15.1).

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

**Abbreviations and acronyms used:**

ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
BCF: Bioconcentration factor.  
CEN: European Committee for Standardization.  
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.  
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.  
EC50: Half maximal effective concentration.  
PPE: Personal protection equipment.  
IATA: International Air Transport Association.  
ICAO: International Civil Aviation Organization.  
IMDG: International Maritime Code for Dangerous Goods.  
LC50: Lethal concentration, 50%.  
LD50: Lethal dose, 50%.  
NOEC: No observed effect concentration.  
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.  
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

**Key literature references and sources for data:**

<http://eur-lex.europa.eu/homepage.html>  
<http://echa.europa.eu/>  
Regulation (EU) 2020/878.  
Regulation (EC) No 1907/2006.  
Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.